



SECTION 34 75 13
OPERABLE ROADWAY EQUIPMENT
ALTERNATIVE SECTIONS 11 12 33 Parking Gates; 32 39 13 Manufactured Metal
Bollards; 34 71 13 Vehicle Barriers

Fast Gate Openers - (Part of the DF Supply, Inc. Family)

www.FastGateOpeners.com

(800) 878-7829

**8500 Hadden Rd.
Twinsburg, OH 44087**

FAAC Group designs manufactures and distributes the most secure, innovative and functional solutions worldwide for every pedestrian and vehicular need: automatic access - parking - access control. FAAC Group satisfies the service and reliability needs of residential, commercial and industrial clients. FAAC Group makes the city move, creating automation that simplifies the lives of those who live there.

Today, after fifty years of business and thanks to steady growth in all areas of automation and access control, FAAC has turned into a large multinational industrial group with more than 1,400 people employed in five continents, 16 manufacturing plants, 30 sales companies in 24 countries and a network of over 80 countries served by official distributors.

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Semi-Automatic Retractable Bollards:**
 - 1. Access Control – Residential restricted areas application Semi-Automatic retractable bollards (Model J200 SA)**

1.2 RELATED REQUIREMENTS

- A. Section 02 22 19 – Traffic Assessment**
- B. Section 32 31 00 – Fences and Gates**
- C. Section 34 71 13 - Paving and Accessories**
- D. Section 03 30 00 - Cast-In-Place Concrete**

1.3 REFERENCES

- A. Submit under provisions of Section 01 42 00 – References**
- B. Abbreviations and Acronyms**
 - 1. SA: Type of Technology used (Semi-Automatic)**

1.4 REGULATORY REQUIREMENTS

**** NOTE ** Delete the standard which are not applicable to your area**

- A. Submit under provisions of Section 01 41 00 – Regulatory Requirements

1.5 SUBMITTALS

- A. Submit under provisions of Section 01 33 00 – Submittal Procedures
- B. Product Data: Provide for each product equipment list, system description and manufacturer's data sheets, including:
 - 1. Product information, manufacturer's names and identification of product.
 - 2. Component connections and details.
 - 3. Storage and handling requirements and recommendations.
- C. Shop Drawings: Submit shop drawings showing layout, product components, including anchorage, excavation details and accessories:
 - 1. Drawings, including wiring diagrams.
 - 2. Risers, layouts, hardware location and accessories predispositions.
 - 3. Special wiring diagrams for optional configurations.
- D. Manufacturer's Instructions:
 - 1. Preparation instructions and recommendations.
 - 2. Operation and installation instructions and manuals.
- E. Manufacturer's Certificates: Certify products meets or exceed specified compliances
- F. Maintenance Data: provide manufacturer's maintenance instructions that include:
 - 1. Lists of periodic checking and maintenance programs
 - 2. Spare parts lists
 - 3. Equipment inter-connection diagrams

1.6 DELIVERY, STORAGE, AND HANDLING

- A. Submit under provisions of Section 01 66 00 – Product Storage and Handling Requirements
- B. Deliver, store and handle materials and products in strict compliance with manufacturer's instructions and industry standards.
- C. Store products indoors in manufacturer's original containers and packaging, with labels clearly identifying product name and manufacturer. Protect from damage.

1.7 QUALITY ASSURANCE

- A. Submit under provisions of Section 01 43 00 – Quality Assurance
- B. Manufacturer Qualifications:
 - 1. ISO 9001 Certified Manufacturer
 - 2. Manufacturer with minimum of 50 year experience
- C. Installer Qualifications: Installation performed by installer specifically trained in bollards operation systems of the type found within this section.
- D. Furnish bollards, all components and accessories by one manufacturer.

1.8 SITE CONDITIONS

- A. Submit under provisions of Section 01 71 00 – Examination and Preparation
- B. Maintain environmental conditions (temperature, humidity, and ventilation) within limits recommended by manufacturer for optimum results. Do not install products under environmental conditions outside manufacturer's absolute limits.
- C. Verify installation required dimensions before installing.
- D. Ensure that excavating surface is appropriate for installation:
 - 1. The characteristic of the ground must guarantee sufficient solidity of the foundation plinth.
 - 2. No tubes or electrical cables should be present in the digging area.

1.9 WARRANTY

**** NOTE ** Apply special warranty provided by local subsidiaries**

- A. Submit under provisions of Section 01 78 00 – Closeout Submittals
- B. Manufacturer's Standard Limited Warranty:
 - 1. Warranty Period: 2 years of free repair or replacement from date of installation
 - 2. Special warranty extensions may apply

PART 2 PRODUCTS

2.1 MANUFACTURERS

- A. Acceptable Manufacturer: FAAC SpA, which is located at: Via Calari, 10 - 40069 Zola Predosa, Bologna – Italy / Tel: (+39)-051-61724 / Fax: (+39)-051-758518 / Email: info@faacgroup.com / Web: www.faacgroup.com
- B. Substitutions: Not permitted
- C. Requests for substitutions will be considered in accordance with provisions of Section 01 25 00 - Substitution Procedures.

2.2 MODEL J200 H600 SA – PAINTED VERSION.

- A. Overall Description: Semi-Automatic retractable bollard. The product is targeted for residential restricted areas traffic regulation.
- B. Actuator
 - 1. Single acting gas spring
- C. Cylinder
 - 1. Height from ground: 600mm / 23.6 inches
 - 2. Diameter: 200 mm / 7.9 inches
 - 3. Material: Steel S235JRG2 EN 10277 (6mm / 0.23 inches thick)
 - 4. Finishing: Anti- corrosive Cathodolysis and polyester powder painted, Dark grey metallized - RAL 7021
 - 5. Head: aluminium, Grey - RAL 9006
- D. Reflective strip
 - 1. Height: 25mm / 0.99 inches
 - 2. Colour: Yellow

- E. Suggested Usage: commercial, industrial and urban restricted areas traffic regulation
- F. Performances
 - 1. Operating by
 - a. Rising: gas spring
 - b. Lowering: manual lowering
- G. Features
 - 1. Weight: 82kg / 180.8 pounds
 - 2. Overall Dimensions: 400 x 500 x 800 mm / 15.7 x 19.7 x 31.5 inches

2.3 MODEL J200 H600 SA – STAINLESS STEEL SATIN FINISHING VERSION.

- A. Overall Description: Semi-Automatic retractable bollard. The product is targeted for residential restricted areas traffic regulation.
- B. Actuator
 - 1. Single acting gas spring
- C. Cylinder
 - 1. Height from ground: 600mm / 23.6 inches
 - 2. Diameter: 200mm / 7.9 inches
 - 3. Material: AISI 316L (6mm / 0.23 inches thick)
 - 4. Finishing: Satin finishing.
 - 5. Head: aluminium. Grey - RAL 9006
- D. Reflective strip
 - 1. Height: 25mm / 0.99 inches
 - 2. Colour: Yellow
- E. Suggested Usage: commercial, industrial and urban restricted areas traffic regulation
- F. Performances
 - 1. Operating by
 - a. Rising: gas spring
 - b. Lowering: manual lowering
- G. Features
 - 1. Weight: 82kg / 180.8 pounds
 - 2. Overall Dimensions: 400 x 500 x 800 mm / 15.7 x 19.7 x 31.5 inches

2.4 ACCESSORIES

**** NOTE ** Add eventual extra accessories**

- A. Provide the optional accessories listed below:
 - 1. Pit heater: to be added to enlarge the operation temperature range to extreme low temperatures (as above specified).
 - 2. Led lights kit: to indicate the bollard upraised position

PART 3 EXECUTION

3.1 EXAMINATION AND PREPARATION

- A. Verify that all site conditions, installation and operating conditions are compliant to the

sections and manufacturer's requirements express in the instructions.

- B. Inspect and prepare substrates and surface properly in accordance to the manufacturer's recommendations.
- C. If preparation is the responsibility of another installer, notify Architect in writing of deviations from manufacturer's recommended installation tolerances and conditions.
- D. Clean surfaces thoroughly prior to installation.
- E. Verify that required drainage and electrical services are in place as required for the installation.
- F. Verify that the product surrounding area is clear from obstacle and flying electric wiring for proper beam motion
- G. It is suggested to provide an adequate protection against accidental impact if product will be exposed to vehicles, when possible

3.2 INSTALLATION

- A. Foundation: Required excavation dimensions: 700 x 700x 1100 mm / 27,6 x 27,6 x 43,3 inches (wide x deep x tall)
- B. Install in accordance with manufacturer's instructions. Test for proper operation and adjust until satisfactory results are obtained.
- C. Clean all metal surfaces promptly after installation.

3.3 FINAL ADJUSTMENT

- A. Check safety devices and compliance to safety regulations, otherwise adjust parameters or replace defective parts until satisfactory results are obtained.

3.4 PROTECTION

- A. Protect installed products until completion of project.
- B. Prevent product from damage.
- C. Touch-up, repair or replace damaged products before Substantial Completion.

END OF SECTION