

HEADQUARTERS

ITALY

FAAC SpA  
Via Calari 10 - 40069 Zola Predosa (BO)  
Tel. +39 051 61724 - Fax +39 051 758518  
it.info@faacgroup.com - www.faacgroup.com

SUBSIDIARIES

AUSTRALIA

FAAC AUSTRALIA PTY LTD  
Homebush – Sydney, Australia  
tel. +61 2 87565644  
fax +61 2 87565677  
www.faac.com.au

AUSTRIA

FAAC GMBH  
Salzburg, Austria  
tel. +43 662 8533950  
fax +43 662 85339525  
www.faac.at

FAAC TUBULAR MOTORS  
tel. +49 30 56796645  
fax +49 30 22409006  
faactm.info@faacgroup.com  
www.faac.at

BENELUX

FAAC BENELUX NV/SA  
Brugge, Belgium  
tel. +32 50 320202  
fax +32 50 320242  
www.faacbenelux.com

FAAC TUBULAR MOTORS  
Schaapweg 30  
NL-6063 BA Vlodrop, Netherlands  
tel. +31 475 406014  
fax +31 475 406018  
faactm.info@faacgroup.com  
www.faacbenelux.com

CHINA

FAAC SHANGHAI  
Shanghai, China  
tel. +86 21 68182970  
fax +86 21 68182968  
www.faacgroup.cn

FRANCE

FAAC FRANCE  
Saint Priest - Lyon, France  
tel. +33 4 72218700  
fax +33 4 72218701  
www.faac.fr

FAAC FRANCE - AGENCE PARIS  
Massy - Paris, France  
tel. +33 1 69191620  
fax +33 1 69191621  
www.faac.fr

FAAC FRANCE - DEPARTEMENT VOLETS  
Saint Denis de Pile - Bordeaux, France  
tel. +33 5 57551890  
fax +33 5 57742970  
www.faac.fr

GERMANY

FAAC GMBH  
Freilassing, Germany  
tel. +49 8654 49810  
fax +49 8654 498125  
www.faac.de

FAAC TUBULAR MOTORS  
tel. +49 30 56796645  
fax +49 30 22409006  
faactm.info@faacgroup.com  
www.faac.de

INDIA

FAAC INDIA PVT. LTD  
Noida – Delhi, India  
tel. +91 120 3934100/4199  
fax +91 120 4212132  
www.faacindia.com

IRELAND

NATIONAL AUTOMATION LTD  
Co. Roscommon, Ireland  
tel. +353 71 9663893  
fax: +353 71 9663890  
www.nal.ie

MIDDLE EAST

FAAC MIDDLE EAST FZE  
Dubai Silicon Oasis Operation Center - Dubai, UAE  
tel. + 971 4 3724190  
fax+ 971 4 3724191  
www.faac.ae

Headquarter & East Coast Operations  
FAAC International Inc.  
5151 Sunbeam Road  
Suites 9-11  
Jacksonville, Florida 32257  
Tel. 866 925 3222 Toll Free  
Tel. 904 448 8952  
Fax 904 448 8958

NORDIC REGIONS

FAAC NORDIC AB  
Perstorp, Sweden  
tel. +46 435 779500  
fax +46 435 779529  
www.faac.se

POLAND

FAAC POLSKA SP.ZO.O  
Warszawa, Poland  
tel. +48 22 8141422  
fax +48 22 8142024  
www.faac.pl

RUSSIA

FAAC RUSSIA  
Moscow, Russia  
www.faac.ru

SPAIN

F.A.A.C. SA  
San Sebastián de los Reyes - Madrid, Spain  
tel. +34 91 6613112  
fax +34 91 6610050  
www.faac.es

SWITZERLAND

FAAC AG  
Altdorf, Switzerland  
tel. +41 41 8713440  
fax + 41 41 8713484  
www.faac.ch

UNITED KINGDOM

FAAC UK LTD.  
Basingstoke - Hampshire, UK  
tel. +44 1256 318100  
fax +44 1256 318101  
www.faac.co.uk

U.S.A.

FAAC INTERNATIONAL INC  
Jacksonville, FL - U.S.A.  
tel. +1 904 4488952  
fax +1 904 4488958

FAAC INTERNATIONAL INC  
Fullerton, California - U.S.A.  
tel. +1 714 446 9800  
fax +1 714 446 9898  
www.faacusa.com

West Coast Operations  
FAAC International Inc.  
357 South Acacia Avenue  
Unit 357  
Fullerton, California 92831  
Tel. 800 221 8278 Toll Free  
Tel. 714 446 9800  
Fax 714 446 9898



# FSL700 - FSW900

## 24VDC Commercial Vehicular Gate Operators



2,000 - 02/2013 The descriptions and illustrations contained in the present brochure are not binding. FAAC reserves the right to undertake product technical modifications without prior notice.

24VDC COMMERCIAL GATE OPERATORS:  
EASY INSTALLATION, FULL FEATURE,  
BUILT-IN BATTERY BACKUP SYSTEM

- Operates vehicular gates for high traffic and residential applications and is ideal for custom homes, apartments, self storage, and other commercial applications.
- Multi-Function battery backup is a standard feature built-in and offers main power fail and low battery control of the gate during a power failure.
- The 24VDC direct drive motor to gearbox design offers high power efficiency while reducing costs and added parts.
- Built in soft start soft stop control offers a smooth, more quiet operation and is easier on the gate and gate installation.
- Simple to install design offers multiple prewired terminals, LED indicators, installation handles, accessory shelves, and is easy to access and set limits.
- Wireless master slave is simple to install and eliminates the need for underground wire.



OPERATOR FEATURES

- Built-in battery backup standard
- Soft Start Soft Stop smooth operation
- Heavy duty gearbox and 24VDC motor direct drive design
- Simple, clean design with less moving parts
- Fail safe design on FSL700 slide gate operator
- Release handle with optional padlock on FSW900 swing gate operator
- Zinc galvanized steel frame with handles for easy installation
- FSW900's clam shell cover can be removed without removing swing arm
- FSL700 uses a UV protected polyethylene cover with lift handle slots
- Easy access limits are simple to set
- Battery & accessory shelves
- Adjustable chain idlers for front, rear, and post mount slide gates
- Industry standard swing arm for swing gate applications
- Plug-in loop detector inputs: reverse, open, center (shadow)
- (2) AC accessory power plugs with GFCI Protection NEW ADD ON
- Built-in 3-Button control for easy setup
- Multiple terminal inputs for simple, clean wire installation
- Maglock, solenoid, external alarm outputs
- Power fail option can open or cycle gate
- Low battery option can open or cycle gate
- Anti-Tailgate & Quick Close features standard
- Wireless master slave option

DIMENSIONS AND TECHNICAL CHARACTERISTICS

General		FSL700 Slide Gate Operator		FSW900 Swing Gate Operator	
Power input	120 VAC, 15A	Gearbox	15:1 Fail Safe	Gearbox	900:1 Fail Secure
Motor	24 VDC	Chain Size	#41, 25ft	Arm type	Industry standard
Power	500 W, 1/2 HP	Chain height - front mount	11" from base	Arm attachment height	17" from base
Power input fuse	5 amp FB	Chain mount options	Front, rear, center	Mounting method	Pad or baseplate
Accessory fuse	4 amp SLB	Travel speed	12 inches/sec	Travel speed	90 degrees in 15 sec
AC accessory outlets	2	Gate capacity	1000 lbs, 40 feet	Gate capacity	800 lbs, 18 feet
Accessory power output	24DC	Shipping weight	125 lbs	Shipping weight	150 lbs
M/S wire	RS432, CAT5 wire	Dimensions	22" H, 18" W, 15" D	Dimensions	18" H, 18.5" W, 23.5" D

